

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

1 Identification

- **Product identifier**
- **Trade name:** P17 Black
- **Article number:** I011035-1
- **Application of the substance / the mixture** Polyester resin
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name: Axson USA, Inc.

- Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

- ehs-us@axson.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1(248) 588-2270
Chemtec 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H335 May cause respiratory irritation.
 Eye Irrit. 2B H320 Causes eye irritation.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Vinyl toluene
Talc (Mg₃H₂(SiO₃)₄)
ethanol

· **Hazard statements**

Flammable liquid and vapour.
Harmful if inhaled.
Causes skin and eye irritation.
May cause cancer.
May cause respiratory irritation.
Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection / face protection.
Wear protective gloves.
Ground/bond container and receiving equipment.
Use only non-sparking tools.
Avoid release to the environment.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Specific treatment (see on this label).
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a poison center/doctor if you feel unwell.
IF exposed or concerned: Get medical advice/attention.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 2
Reactivity = 0

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	2	Fire = 2
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	25-50%
CAS: 25013-15-4 EINECS: 246-562-2	Vinyl toluene	10-<20%
CAS: 64-17-5 EINECS: 200-578-6	ethanol	0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect from heat.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

25013-15-4 Vinyl toluene

PEL Long-term value: 480 mg/m³, 100 ppmREL Long-term value: 480 mg/m³, 100 ppm

(Contd. on page 5)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 4)

TLV	Short-term value: 483 mg/m ³ , 100 ppm Long-term value: 242 mg/m ³ , 50 ppm
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Highly viscous

Color: Black

· **Odor:** Pungent

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 999 °C (1830 °F)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 5)

· Flash point:	53 °C (127 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	2.0671 g/cm ³ (17.25 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	14.6 %
VOC content:	14.6 %
	300.9 g/l / 2.51 lb/gl
· Solids content:	59.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA
(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Oral	LD50	4000 mg/kg (rat)
Dermal	LD50	4500 mg/kg (rabbit)
Inhalative	LC50/4 h	3000 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2B
25013-15-4	Vinyl toluene	3
64-17-5	ethanol	1
108-10-1	4-methylpentan-2-one	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:** Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015



Trade name: P17 Black

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, IMDG, IATA 	UN1866
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG, IATA 	Resin solution RESIN SOLUTION
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · IMDG, IATA 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · EMS Number: 	Warning: Flammable liquids F-E,S-E
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 8)

· UN "Model Regulation": UN1866, Resin solution, 3, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-10-1 4-methylpentan-2-one

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

108-10-1 4-methylpentan-2-one

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

64-17-5 ethanol

108-10-1 4-methylpentan-2-one

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
-----------	--------------------------	-----------------------

108-10-1	4-methylpentan-2-one	I
----------	----------------------	---

142-82-5	heptane	D
----------	---------	---

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (Mg3H2(SiO3)4)	A4
------------	---------------------	----

25013-15-4	Vinyl toluene	A4
------------	---------------	----

64-17-5	ethanol	A3
---------	---------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

· **Hazard-determining components of labeling:**

Vinyl toluene

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 9)

Talc (Mg₃H₂(SiO₃)₄)

ethanol

· Hazard statements*Flammable liquid and vapour.**Harmful if inhaled.**Causes skin and eye irritation.**May cause cancer.**May cause respiratory irritation.**Harmful to aquatic life with long lasting effects.***· Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Use explosion-proof electrical/ventilating/lighting/equipment.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wear protective gloves / eye protection / face protection.**Wear protective gloves.**Ground/bond container and receiving equipment.**Use only non-sparking tools.**Avoid release to the environment.**Take precautionary measures against static discharge.**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Specific treatment (see on this label).**IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.**Call a poison center/doctor if you feel unwell.**IF exposed or concerned: Get medical advice/attention.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**In case of fire: Use for extinction: CO₂, powder or water spray.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 07/13/2015 / 7**· Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 07/13/2015

Reviewed on 07/13/2015

Trade name: P17 Black

(Contd. of page 10)

*EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**Flam. Liq. 3: Flammable liquids, Hazard Category 3**Acute Tox. 4: Acute toxicity, Hazard Category 4**Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2**Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B**Carc. 1A: Carcinogenicity, Hazard Category 1A**STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3**Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3*

USA