

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

1 Identification

- **Product identifier**
- **Trade name:** EPOLAM 2015 Hardener
- **Article number:** I022302
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Company Name: Axson USA, Inc.

- Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

- ehs-us@axson.com
- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1(248) 588-2270
Chemtec 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: **EPOLAM 2015 Hardener**

(Contd. of page 1)

· **Hazard pictograms**

GHS05 GHS07 GHS09

· **Signal word** *Danger*· **Hazard-determining components of labeling:***3-aminomethyl-3,5,5-trimethylcyclohexylamine**Polyoxypropylenediamine**alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl))**Trimethylolpropane poly(oxypropylene)tria**mine*· **Hazard statements***Harmful if swallowed, in contact with skin or if inhaled.**Causes severe skin burns and eye damage.**May cause an allergic skin reaction.**May cause respiratory irritation.**Very toxic to aquatic life.**Very toxic to aquatic life with long lasting effects.*· **Precautionary statements***Do not breathe dusts or mists.**Wear protective gloves.**Wear protective gloves / protective clothing.**Wear eye protection / face protection.**Avoid release to the environment.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Use only outdoors or in a well-ventilated area.**Contaminated work clothing must not be allowed out of the workplace.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Immediately call a poison center/doctor.**Specific treatment (see on this label).**If swallowed: Call a poison center/doctor if you feel unwell.**IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.**Wash contaminated clothing before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**If swallowed: Rinse mouth. Do NOT induce vomiting.**Collect spillage.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Store in a well-ventilated place. Keep container tightly closed.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)***Health = 3**Fire = 1**Reactivity = 0*

(Contd. on page 3)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: **EPOLAM 2015 Hardener**

(Contd. of page 2)

- **HMIS-ratings (scale 0 - 4)**

HEALTH	4	Health = 4
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	25-50%
CAS: 39423-51-3	Trimethylolpropane poly(oxypropylene)tri- amine	25-50%
CAS: 9046-10-0	Polyoxypropylenediamine alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2- ethanediyl))	25-50%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
· **Most important symptoms and effects, both acute and delayed** No further relevant information available.
· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 4)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Liquid
Color:	Colorless
Odor:	Characteristic
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	232 °C (450 °F)

- **Flash point:** 95 °C (203 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 320 °C (608 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower:	0.7 Vol %
---------------	-----------

(Contd. on page 6)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: **EPOLAM 2015 Hardener**

(Contd. of page 5)

Upper:	5.0 Vol %
· Vapor pressure at 20 °C (68 °F):	6.8 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	0.9476 g/cm ³ (7.908 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**39423-51-3 Trimethylolpropane poly(oxypropylene)tri-
amine**

Oral	LD50	550 mg/kg (rat)
------	------	-----------------

Dermal	LD50	>1000 mg/kg (rat)
--------	------	-------------------

9046-10-0 Polyoxypropylenediamine

alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl))

Oral	LD50	2855 mg/kg (rabbit)
------	------	---------------------

Dermal	LD50	2980 mg/kg (rabbit)
--------	------	---------------------

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
Strong caustic effect.
Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 7)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 6)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Ecotoxic effects:**

· **Remark:** Very toxic for fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS






Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 7)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT · IMDG, IATA 	<p>NA2735 UN2735</p>
<ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG · IATA 	<p><i>Amines, liquid, corrosive, n.o.s. (Isophoronediamine, Polyoxypropylenediamine alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl)))</i></p> <p>A M I N E S , L I Q U I D , C O R R O S I V E , N . O . S . <i>(ISOPHORONEDIAMINE, Polyoxypropylenediamine alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl))), MARINE POLLUTANT</i></p> <p>A M I N E S , L I Q U I D , C O R R O S I V E , N . O . S . <i>(ISOPHORONEDIAMINE, Polyoxypropylenediamine alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl)))</i></p>
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="display: flex; align-items: center; gap: 10px;">   </div> <p>8 Corrosive substances</p>
<ul style="list-style-type: none"> · Class · Label 	<p>8 8</p>
<ul style="list-style-type: none"> · IMDG 	<div style="display: flex; align-items: center; gap: 10px;">   </div> <p>8 Corrosive substances</p>
<ul style="list-style-type: none"> · Class · Label 	<p>8 8</p>
<ul style="list-style-type: none"> · IATA 	<div style="display: flex; align-items: center; gap: 10px;">  </div> <p>8 Corrosive substances</p>
<ul style="list-style-type: none"> · Class · Label 	<p>8 8</p>
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	<p><i>Product contains environmentally hazardous substances: Trimethylolpropane poly(oxypropylene)tria mine</i></p> <p><i>Yes</i> <i>Symbol (fish and tree)</i></p>
<ul style="list-style-type: none"> · Special precautions for user 	<p><i>Warning: Corrosive substances</i></p>

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 8)

· Danger code (Kemler):	80
· EMS Number:	F-A,S-B
· Segregation groups	Alkalis
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· Remarks:	Special marking with the symbol (fish and tree).
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN2735, Amines, liquid, corrosive, n.o.s. (Isophoronediamine, Polyoxypropylenediamine alpha-(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl))), ENVIRONMENTALLY HAZARDOUS, 8, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: **EPOLAM 2015 Hardener**

(Contd. of page 9)

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS05 GHS07 GHS09

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Polyoxypropylenediamine

 α -(2-Aminomethylethyl)-omega-(2-aminomethylethoxy)-poly(oxy(methyl-1,2-ethanediyl))

Trimethylolpropane poly(oxypropylene)tria

mine

· **Hazard statements**

*Harmful if swallowed, in contact with skin or if inhaled.**Causes severe skin burns and eye damage.**May cause an allergic skin reaction.**May cause respiratory irritation.**Very toxic to aquatic life.**Very toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

*Do not breathe dusts or mists.**Wear protective gloves.**Wear protective gloves / protective clothing.**Wear eye protection / face protection.**Avoid release to the environment.**Wash thoroughly after handling.**Do not eat, drink or smoke when using this product.**Use only outdoors or in a well-ventilated area.**Contaminated work clothing must not be allowed out of the workplace.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Immediately call a poison center/doctor.**Specific treatment (see on this label).**If swallowed: Call a poison center/doctor if you feel unwell.**IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.**Wash contaminated clothing before reuse.**If skin irritation or rash occurs: Get medical advice/attention.**If swallowed: Rinse mouth. Do NOT induce vomiting.**Collect spillage.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Store in a well-ventilated place. Keep container tightly closed.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/12/2015

Reviewed on 05/11/2015

Trade name: EPOLAM 2015 Hardener

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/12/2015 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

USA