



SDS

Chemline Incorporated

CHEMLINE RF02.5 S45 PT B NEUTRAL

1	PRODUCT AND COMPANY IDENTIFICATION
---	---

Supplier Details: Chemline Incorporated
5151 Natural Bridge Road
Saint Louis, MO 63115

Emergency: CHEMTREC 800-424-9300 (24 HOUR SERVICE)

Phone: 314-664-2230

Fax: 314-664-1355

Web: www.chemline.net

2	HAZARDS IDENTIFICATION
---	-------------------------------

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

No GHS Classifications Indicated

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **NONE**

No GHS pictograms indicated for this product

GHS Hazard Statements:

No GHS hazards statements indicated

GHS Precautionary Statements:

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash skin thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
P330 - Rinse mouth.
P403+233 - Store in a well ventilated place. Keep container tightly closed.
P405 - Store locked up.
P501 - Dispose of contents/container according to state, local and federal regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Inhalation; Skin;

Target Organs: Eyes; Skin; Respiratory system;

Inhalation: Heating, spraying, foaming or otherwise mechanically dispersing operations may generate vapor or aerosol concentrations sufficient to cause irritation or other adverse effects. Minimal respiratory tract irritation may occur with exposure to a large amount of material.

Skin Contact: Prolonged or repeated exposure can cause skin irritation or dermatitis in some individuals.

Eye Contact: May cause watering of the eye and irritation of the conjunctiva.

Ingestion: May cause nausea or vomiting.

3	COMPOSITION/INFORMATION OF INGREDIENTS
---	---

Ingredients:

Cas#	%	Chemical Name
0	95-100%	Proprietary polyol blend

4	FIRST AID MEASURES
---	---------------------------

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.

Skin Contact: Remove all contaminated clothing and shoes. Wash skin with large quantities of water and soap. Wash clothing before wearing again and clean shoes. If redness, itching or a burning sensation develops or persists after the area is washed, consult a physician.

Eye Contact: Flush with large amounts of water for 15 minutes. Use fingers to assure that the eyelids are separated and that the eye is being irrigated. Get immediate medical attention.

Ingestion: If swallowed, do not induce vomiting unless directed to do so by medical personnel. This material is an aspiration hazard. Never give anything by mouth to an unconscious person. Seek medical attention.

5	FIRE FIGHTING MEASURES
---	-------------------------------

Flash Point: >200°F
Flash Point Method: COC

Dry powder, foam, carbon dioxide. Use cold water spray to cool fire exposed containers to minimize risk of rupture. A solid stream of water directed into hot burning liquid could cause frothing. If possible, contain fire run off.

6	ACCIDENTAL RELEASE MEASURES
---	------------------------------------

Spill: Remove all sources of flames, heating elements, gas engines, etc. Emergency clean-up personnel should wear chemical goggles, rubber or plastic gloves and clothing as required to protect against contact. Prevent spreading and contamination of surface waters and drinking supplies. Notify local health officials and other appropriate agencies if such contamination should occur.

Clean up: With adequate ventilation and appropriate personal protective equipment, cover the area with an inert absorbent material such as clay or vermiculite and transfer to steel waste containers. Ventilate area to remove the remaining vapors.

7	HANDLING AND STORAGE
---	-----------------------------

Handling Precautions: Do not smoke or use naked lights, open flames, space heaters or other ignition sources near pouring, frothing or spraying operations. If contamination with isocyanates is suspected, do not reseal containers. Special Emphasis for spray applications of mixed products containing isocyanates: Inspect the application area for potential to expose other persons or for overspray to drift onto buildings, vehicles or other property. When spraying building exteriors, persons entering or exiting the building as well as those inside could be exposed to polyisocyanates due to wind conditions, open windows or air intakes. Do not begin application work until these potential problems have been corrected.

Storage Requirements: When stored between 60°-85° F in sealed containers, typical shelf life is 6 months or more from the date of manufacture. Open containers must be handled properly to prevent moisture pickup.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
---	--

Engineering Controls: All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Uses requiring heating and/or spraying may require more aggressive engineering controls or PPE.

Personal Protective Equipment: HMIS PP, X | Consult your supervisor for special instructions

Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and

approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Splash contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 30 min Material tested: Butoject (KCL 897 / Aldrich Z677647, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

None available

9	PHYSICAL AND CHEMICAL PROPERTIES
---	---

Appearance:	Non-Pigmented liquid.	Odor:	Mild
Physical State:	Liquid	Flash Point:	>200°F
Spec Grav./Density:	N/A	Vapor Density:	>1
Boiling Point:	>500°F		
Flammability:	None Flammable		
Evap. Rate:	<1		

10	STABILITY AND REACTIVITY
----	---------------------------------

Reactivity:	No specific data
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	No specific data
Materials to Avoid:	No specific data
Hazardous Decomposition:	Under normal storage conditions hazardous decomposition products should not be produced.
Hazardous Polymerization:	Will not occur.

11	TOXICOLOGICAL INFORMATION
----	----------------------------------

None available

12	ECOLOGICAL INFORMATION
----	-------------------------------

None available

Disposal: Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

Non DOT/Non RCRA regulated

Component (CAS#) [%] - CODES

Proprietary polyol blend (0) [85-95%] IARC


Regulatory CODE Descriptions

IARC = IARC Carcinogen Risks

NFPA: Health = 1, Fire = 1, Reactivity = 0, Specific Hazard = None

HMIS III: Health = 1, Fire = 1, Physical Hazard = 0

HMIS PPE: X - Consult your supervisor for special instructions



Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).